

Stationary concrete pump

BSA 1409 D5

Output up to 98 m³/h
Delivery pressure up to 109 bar



Note: Standard version. Dimensions and weights depend on equipment. Subject to technical modifications and errors.

Technical data

Model		BSA 1409 D5
Material number		103110.000
Output	m ³ /h	98 / 66*
Delivery pressure	bar	73 / 109*
Delivery cylinder	Ø mm	200
Delivery cyl. stroke	mm	1400
Strokes / minute		37 / 25*
Engine power	kW	180
Hopper		RS 909
Capacity	l	approx. 600
Filling height	m	1.49
Transfer tube		S 2015 D
Line connection	mm	SK 125
Pressure connection	"	5.5
Control system		Ergonic 3 FFH
Weight approx.	kg	5500

* Values for hydraulic fluid being fed to piston-side
All data maximum theoretical

Serial equipment

Agitator safety switch off	Flushing water pump
Cable remote control 10 m	50 l/min 20 bar
Central lubrication on hopper with grease gun	Gate valve connection
Cleaning accessories	Grill 60 mm
Coloring: Pump, frame and roof anthracite-grey; cover chrome yellow	Operating manuals and spare part list
Concrete hopper with agitator	Outriggers 4× mech.
Concrete output adjust	Pump flow meter
Concrete pressure adjust	Reduction elbow 90°; SK 150 → SK 125
Drawbar eye (DIN)	Speed drawdown automatically on pump stop
Drive diesel, Deutz 180 kW, Stage V	Splash guard foldable
Electronic error management	Support wheel
Ergonic Graphic Display (EGD)	Tool set incl. standard equipment
	Trailer F8, can be driven on site

See quotation for exact serial delivery scope.
Comprehensive range of options available on request.